

STONIMAGE

How to be A Global Leader in Services?

Many of us are facing after-sales trouble no matter private or governmental control company, time is invaluable and most worrying for us. Once the machine shut down, the production shut down either, and we start to lose money quickly and come to an operation crisis So what we do here?

- ◆ Fast Action in Services
- ◆ Unconditional Parts Supply
- ◆ Strong Professionalism
- ◆ Spotless Satisfaction

This is how STONIMAGE started to make business. What we do is giving the fastest services after supplying high-quality level products.

XINXIANG STONIMAGE TECHNOLOGY CO. LTD

新乡市石像科技有限公司

Email: inquire@stonimage.com

Tel: +86 373 5853611 +86 173 3736 9213

www.stonimagelift.com

Add: 1522#, Gongyuanguoji, Hongqi district, Xinxiang city, Henan, China

STONIMAGE

was founded at end of 2014, is a global brand and manufacturer of lifting equipment and material handling equipment, we owns the most professional engineering team, R & D center and manufacturing base with rich experience in lifting industry. We are working with full passion in continuous innovation and improving services level.

Currently, STONIMAGE is focusing on Innovation, Manufacturing and Supplying of various lifting equipment, transportation machinery and construction machinery, mainly as below:

- Ladder Lift, Solar Panel Lift, Glass and window lift, Glass trolley
- Cargo truck elevator, Fish elevator, Mountain cargo Lift
- Electric scaffold, Wall building platform
- Electric forklift, Brick stacker, Installation Forklift for Pipe/Panel
- Scissor lift, Retractable stairs, Belt conveyor
- Restaurant Meal elevator



- **Aerial Ladder Lift**
- ✓ For Solar panel
- ✓ For Glass/window/door
- ✓ For Construction material



- **Cargo Truck Loader**
- **Fish Truck Loader**

Roller shutter door Lift

- ✓ Max. Lifting Capacity: 150kg
- ✓ Lifting height: 3.8 ~ 5.0m
- ✓ For lifting roller shutter door



Technical Data

Platform Height (m)	Max. Lifting Capacity (kg)	Frame height (cm)	Base plate size (cm)	Dead weight (kg)
3.8	150	113	60*60	40
4.5	150	133	60*60	45
5.0	150	143	60*60	48

Technical Notes:

- 1) Motor power: 1150w
- 2) Control: Pendent Control+ Remote control
- 3) Wire Rope diameter: 5mm, galvanized
- 4) Packing: Wooden case (especially for export)

Application
应用案例

